


CarTAG – CarCommunication via RFID

Data generation

- mileage
- Fill levels
- operational time
- Telemetry
- VIN
- Fault memory
- Diagnosis
- User
-

Data analysis

- Driving data
- Diagnosis data
- Identification
-




CarTAG – CarCommunication via RFID

- UHF EPC C1 Gen2 conform
- Standard RFID-infrastructure
- To the outside: a passive Gen2 TAG
- To the inside: a communication device with the vehicle bus
- Interesting for car parks, rental cars, freight forwarders, taxis ...
- Automatic transmission of vehicle data
- Offline parameter setting
- Customized firmware on request


CarTAG – CarCommunication via RFID

- UHF - Standard RFID-TAG
- EPC 128 bit
- Datarate up to 640 kbit/s
- e.g. FRAM - User-Memory 1,5 kByte
- Authentication with password
- Configuration of Memorysegments
- Encryption e.g. with AES 128 bit
- Active: < 10 mA on board voltage
- Halt Mode < 1 mA
- CAN up to 500 kBaud



CarTAG – CarCommunication via RFID

- ODB 2 standard commands
- CAN messages with any control devices
- Memory config: Lock for read/write
- Memory mapping Plain / Secure
- e.g. AES encryption of stored data Key transfer during installation
- Secret key in database



CarTAG – CarCommunication via RFID

Application examples

Rental Cars

On return, when an antenna is crossed, mileage, tank filling, exceeding of other operating parameters are detected automatically

Car workshops

The vehicle is detected at the entrance and fault conditions are transmitted directly - when the customer disembarks, all important information is available to the customer service staff

Immobilizer on the parking lot of the manufacturer

Vehicles can be blocked or unlocked in the parked state

Machine maintenance

Machines such as elevator systems or machine tools can also be maintained and parameterized by means of RFID from a handheld device via this system

CarTAG – CarCommunication via RFID

Functional Prototype

